

APPLICATION FOR UNITED STATES PATENT

Inventors: **ROBERT MUELLER and
FRANZ-JOSEF VOGELSANG**

Invention: **SWITCH, ESPECIALLY FOR BRANCHING OFF BULK
MATERIAL FLOWS**

**William D. Breneman, Esq.
BRENEMAN & GEORGES
3150 Commonwealth Avenue
Alexandria, Virginia 22305
Telephone : (703) 683-8006
Facsimile: (703) 683-8009**

SPECIFICATION

"Switch, especially for branching off bulk material flows"

5 The invention relates to a diverter switch, in particular a single-channel diverter switch, for branching off bulk-material flows, having a rotary plug which is arranged in a stationary housing preferably comprising three connecting openings according to the preamble of Claim 1.

10

Prior art

15 Numerous different variants of diverter switches, in particular single-channel diverter switches or plug diverter switches, are already known. They generally have the task of feeding the bulk material to be conveyed to various pipelines by deflecting the conveying direction, a conveying gas in particular being used for conveying the bulk material.

20

In a corresponding diverter switch according to publication DE 39 22 240 C2, a cylindrical rotary plug is used, in which the inlet side and outlet side of the through-channel are transposed by the adjustment or
25 rotation from a first position into a second position. In this case, flow occurs through the through-channel of the rotary plug in the second position against the direction of flow of the conveying fluid in the first position. The through-channel is arranged essentially
30 perpendicularly to the rotation axis of the cylindrical rotary plug and often has a virtually round free cross section.

35 In corresponding single-channel diverter switches, depending on the length of the conveying path downstream of the deflection or downstream of the valve, considerable pressure differences can partly occur between the two outflow channels. Corresponding diverter switches normally have elastic seals in order

to minimize leakages which occur. In this case, the leakages depend, inter alia, on the pressure of the conveying fluid or transport gas in comparison with the atmospheric ambient pressure and also on the above-mentioned pressure differences between the outflow channels.

Corresponding seals may be accommodated in the diverter switch housing or in the rotary plug. For example, these seals are designed as inflatable seals or as static seals, in particular provided with a special profile shape, which press automatically against the mating body when pressure builds up in the conveying line.

A disadvantage with corresponding sealing systems, however, is that seal wear may occur, the corresponding seals being partly abraded. Since the seal material normally cannot be made of the same material as the bulk material to be conveyed, the abrasion of the seal leads to contamination of the material to be conveyed. In the case of very high-grade materials to be conveyed, or materials to be conveyed which are of very high purity, this abrasion is disadvantageous or even inadmissible. Used for such special applications are diverter switches which have as narrow a gap as possible between the plug and the housing in order thus to reduce the leakage losses.

In terms of construction, very high demands are made on the accuracy and guidance of the components, so that the established gap is retained in all operating states and material contact and possibly seizing or abrasion does not occur. The realization of comparatively narrow gaps between the plug and the housing therefore requires the plug and also the housing to be produced in a very complicated manner to close tolerances, which leads to economically unfavourable production of corresponding diverter switches.

In addition, the gaps which can currently be realized lead to unacceptable leakage losses in particular in plug diverter switches working under relatively high pressure differences. This may lead, for example, to malfunctions in the conveying operation, which has to be compensated for at considerable cost, if need be by additional, metered feeding of conveying gas directly downstream of the diverter switch. Sealing closure members connected downstream will possibly be necessary in the case of corresponding diverter switches, which likewise leads to an increase in the cost.

Object and advantages of the invention

Against this background, the object of the invention is to propose a diverter switch for branching off bulk-material flows which does not have the disadvantages of the prior art and permits optimum sealing of the rotary plug even without additional contact sealing elements.

Starting from a diverter switch of the type mentioned at the beginning, this object is achieved by the characterizing features of Claim 1.

Advantageous embodiments and developments of the invention are possible by the measures mentioned in the subclaims.

Accordingly, the diverter switch according to the invention is characterized by the fact that the rotary plug and/or the housing has at least one labyrinth seal arrangement.

By means of such a labyrinth seal arrangement, a non-contact seal can advantageously be realized between the rotary plug and the housing, i.e. without an additional, separate seal, which is subjected to abrasion, being used in the process. In contrast to a

contact seal, in which the seal surfaces touch one another and are generally pressed against one another, contact between the sealing surfaces is completely prevented in the case of a non-contact seal. On the
5 contrary, according to the invention, the sealing effect is realized by the flow resistance of the substance to be sealed off by means of the free gap with labyrinth seal arrangement.

10 In a labyrinth seal arrangement or a labyrinth-gap seal arrangement, the pressure of the fluid in a chamber, widened section, recess or the like is advantageously reduced by vortex formation and throttling, a factor which, for example, in a labyrinth seal comprising a
15 plurality of chambers, leads to the gradual pressure drop from chamber to chamber.

If need be, the labyrinth seal arrangement can be formed by an integrally formed portion, coating, inlay,
20 etc., which is preferably made of the material of the rotary plug or housing or of a comparable material. In a preferred embodiment of the invention, the labyrinth seal arrangement is designed as a recess, chamber, in particular as a labyrinth seal groove, in the rotary
25 plug or housing. By means of an appropriate recess or groove, the seal according to the invention can be realized without a further, separate, or additional seal component. In this case, it is advantageous that, in an especially simple manner, with a contact seal
30 element being dispensed with, it is absolutely certain that contamination or impairment of the bulk-material flow or conveying fluid cannot occur, and at the same time an advantageous sealing effect can be realized. According to the invention, the housing is thereby
35 effectively sealed off relative to the rotary plug, so that leakages can be decisively reduced or completely or virtually prevented.

A plurality of labyrinth seal grooves arranged next to one another are advantageously provided. For example, about three to ten or more seal grooves are provided per seal. Each groove leads to a pressure drop, so that
5 the sealing effect is improved with increasing number of grooves. The number of seal grooves is advantageously adapted to the cost of realizing corresponding grooves.

10 In a special development of the invention, the labyrinth seal groove of the rotary plug is arranged largely continuously around at least one opening of a through-channel. In special applications, a labyrinth seal groove which is interrupted at least once and is
15 generally arranged around the opening of the through-channel is conceivable; for example, particular sections of the rotary plug are realized with additional, corresponding labyrinth seal grooves. An advantage with these developments of the invention is
20 that only two labyrinth seal arrangements, i.e. in each case one arrangement per opening of the through-channel, is required for realizing a fully sealed-off single-channel diverter switch.

25 Alternatively, or in combination with the aforesaid developments of the invention, the labyrinth seal groove of the housing may be arranged largely continuously around at least one of the connecting openings. In accordance with the aforesaid
30 developments, a labyrinth seal groove interrupted at least once or designed so that it is not closed is also conceivable in this case, this labyrinth seal groove possibly being additionally arranged at particular sections of the housing.

35 In an advantageous embodiment of the invention, the housing is designed in such a way that it has in each case at least one labyrinth seal arrangement around each connecting opening. In these embodiments, there

are therefore at least three corresponding labyrinth seal arrangements, so that at least two labyrinth seal arrangements are provided between two connecting openings. In this case, the third connecting opening,
5 which is not involved in the conveying operation, is also additionally sealed off in an advantageous manner, so that the sealing effect in particular between the corresponding connecting openings is further improved, which additionally increases the operating reliability
10 of the diverter switch according to the invention.

In a special development of the invention, at least one feed opening of a feed channel for feeding a suitable gap fluid into the region of the gap is provided. The
15 diverter switch can be advantageously flushed by feeding a gap fluid into the gap between housing and plug. For example, gap fluid is fed to the gap at least in a rotary or adjusting phase of the rotary plug. Gap fluid can possibly be fed to the gap almost
20 continuously and/or during the entire conveying operation.

By the feeding of the gap fluid into the gap according to the invention, relatively fine material to be
25 conveyed, for example, can be advantageously transported or blown back from the region between rotary plug and housing into the through-channel or into a conveying channel arranged at a connecting opening. By means of this measure, an outflow of the
30 conveying fluid and/or escape of some of the bulk-material flow is prevented to the greatest possible extent. A corresponding feed opening for feeding a gap fluid into the region of the gap is generally advantageous in a diverter switch according to Claim 1.

35 In an advantageous embodiment of the invention, the labyrinth seal groove has the feed opening. By this measure, the labyrinth seal groove is designed as a distributing groove for distributing the gap fluid at

least over the entire length of the groove or advantageously around the circumference of the opening of the through-channel or around the connecting opening.

5

A pressure of the gap fluid is advantageously greater than a pressure of the conveying fluid, so that it can be ensured that no conveying fluid or bulk material can pass through the gap into the intermediate space
10 between housing and rotary plug.

If need be, the gap fluid essentially comprises an inert or less active substance. For example, the gap fluid used is commercially available nitrogen or the
15 like.

In a special development of the invention, a composition of the gap fluid essentially corresponds to a composition of the conveying fluid. By means of this
20 measure, contamination of the conveying fluid and/or of the bulk-material flow to be conveyed is advantageously ruled out to the greatest possible extent.

Numerous feed openings at a distance from one another
25 can preferably be arranged around a connecting opening and/or an opening of the through-channel. For example, a labyrinth seal groove comprises an appropriately large number of feed openings. In principle, by means of an appropriate feed of a gap fluid into the region
30 of the gap, a fluid curtain or the like for screening off or sealing off the gap to the greatest possible extent can be realized.

In a preferred embodiment, a maximum width of the gap
35 between housing and rotary plug is smaller than or equal to 5/10ths of a millimetre, preferably smaller than or equal to 3/10ths of a millimetre. Especially in combination with the labyrinth seal arrangement according to the invention, it has been found in

practice that a corresponding gap represents an especially advantageous embodiment of the invention.

Exemplary embodiment

5

An exemplary embodiment of the invention is shown in the drawing and explained in more detail below with reference to the figures.

10 In the drawing, in particular:

Figure 1 shows a schematic sectional representation through a single-channel diverter switch according to the invention in a first position,
15

Figure 2 shows a schematic sectional representation of the single-channel diverter switch according to the invention in a second position,
20

Figure 3 shows a schematic, enlarged detail of a labyrinth seal according to the invention,

Figure 4 shows a schematic, perspective, partly sectioned representation of the single-channel diverter switch according to the invention,
25

Figure 5 shows a schematic, perspective representation of a rotary plug according to the invention,
30 and

Figure 6 shows the rotary plug according to Figure 5 in plan view.

35 A single-channel diverter switch according to the invention, having a cylindrical rotary plug 1 and a correspondingly adapted housing 2, is presented in Figure 1 in a sectioned representation. Instead of a cylindrical rotary plug in the cylindrical housing,

another adapted shape, such as a spherical shape for example, may also be used. The rotary plug 1 is located in a first position, so that a passage by means of a channel 3 is realized from a first connecting line 4 to a second connecting line 5.

A second position of the cylindrical rotary plug 1 according to the invention is shown in Figure 2, the channel 3 permitting a connection between the connecting line 4 and a third connecting line 6. The cylindrical rotary plug 1 is adjusted by means of a rotation about a rotation axis D arranged essentially perpendicularly to the channel 3, it being possible for the rotary plug 1 to rotate in directions of rotation R.

According to the invention, the cylindrical housing 2 and/or the cylindrical rotary plug 1 comprises a labyrinth seal arrangement 7. For reasons of clarity, only the rotary plug 1 with the seal 7 according to the invention is presented in Figures 1 and 2.

On the other hand, schematically shown in the detail "X" in Figure 3 is an embodiment in which both the rotary plug 1 and the housing 2 have a labyrinth seal 7. It becomes clear with the aid of Figure 3 that the seal 7 presented in each case consists of three grooves 8 or 9, respectively. The grooves 8 of the rotary plug are advantageously staggered relative to the grooves 9 in the direction of flow F. An arrangement in which the grooves 8 and 9 are arranged opposite one another is likewise conceivable.

In addition, it becomes clear in Figure 3 that the rotary plug 1 is at a distance from the housing 2 and as a result a gap 10 realized between housing 2 and rotary plug 1 and having a gap width W is formed. A conveying gas (not shown in any more detail) flows according to arrow F into the gap 10 and is swirled by

means of the grooves 8, 9, so that a non-contact seal 7 is advantageously realized.

According to Figure 4, the single-channel diverter switch is presented in a perspective, partly sectioned representation. Here, it becomes clear that the single-channel diverter switch has two side covers 11, in particular for mounting the rotary plug 1. If need be, a seal (not shown in any more detail) which is possibly also elastic may be provided between at least one side cover 11 and the housing 2 and/or the rotary plug 1. Alternatively, or in combination with this, at least one side cover 11 may be sealed off relative to the housing 2 and/or the rotary plug 1 by means of a labyrinth seal 7 according to the invention.

The three-dimensional design of the rotary plug 1 including the two seals 7 for sealing off the openings of the through-channel 3 is illustrated in Figure 5. The grooves 8 of the seals 7 can be produced, for example, by means of a cutting, abrasive or comparable process in a comparatively simple manner, preferably by means of electronically controllable machine tools.

According to Figure 5, a centre groove 8 of the seal 7 has two flushing openings 12, through which a flushing fluid or commercially available nitrogen can be introduced into the gap 10 by means of a flushing channel (not shown in any more detail) of the rotary plug 1. In this way, in particular the centre groove 8 is designed as a distributing channel for distributing the flushing fluid around the opening of the through-channel 3 of the rotary plug 1.

In general, the grooves 8 or 9, as shown, may be designed as continuous grooves 8, 9 or, in a manner not shown in any more detail, as grooves 8, 9 which are interrupted at least once.

Figure 6 shows the rotary plug 1 in plan view. For example, the grooves 8 and/or 9, as in Figures 5, 6, are arranged concentrically to one another.

- 5 In a manner not shown in any more detail, further seals may be provided, for example, in the marginal region 13 of the lateral surface of the rotary plug 1, between the seals 7 of the rotary plug, between the seals 7 of the housing 2, etc. It is also conceivable to realize a
10 sealing system or the like by means of a network of grooves 8, 9 or the like arranged on the housing 2 and/or the rotary plug 1.

- A seal variant encloses the plug laterally at the
15 circumference and avoids the overflow of the conveying gas into the region of the lateral cover, so that leakages occur only via the gap at the plug circumference; another variant encloses the respective conveying channels completely.

- 20 The invention is not restricted to the exemplary embodiment shown and described. On the contrary, it also comprises all variants within the scope of the patent claims.

List of designations:

	1	Rotary plug
	2	Housing
5	3	Channel
	4	Connecting line
	5	Connecting line
	6	Connecting line
	7	Seal
10	8	Groove
	9	Groove
	10	Gap
	11	Side cover
	12	Gap opening
15	13	Margin
	D	Rotation axis
	F	Direction of flow
	R	Direction of rotation
20	W	Gap width
	X	Detail